

07-12-2016

SOUTH EAST CENTRAL RAILWAY

Page 1 of 6

STORES DEPARTMENT

SUPPLY OF STORES ITEMS

**TENDER NOTICE No : E-34/2016-17**

**Date:** 07-12-2016

SECR has implemented e-procurement system. The following tenders will be dealt through E-procurement only. No manual/postal offers will be entertained. These tenders with full details can be accessed under the link [www.ireps.gov.in](http://www.ireps.gov.in). . Cost of Tender document and EMD through DD in favour of FA&CAO/SECR/Bilaspur payable at Bilaspur can be sent by post duly indicating the relevant tender no., tender opening date & tender type overleaf and super scribing "Cost of Tender Document and EMD cost for E-procurement Tender No. ., due on . ." on the envelop to the office of the Controller of stores, SECR, G.M. Office Building, GF, Bilaspur - 495-004 before the closing date and time. Tender closing time is 10.30 hrs.

Sr.No	Tender No	Tender Opening Date	Description	QTY	Tender Cost	Emd Amount
1	04161193	05-JAN-17	(PL_NO:45147012) Uninsulated cadmium copper catenary wire (19/2.10 mm), 65 Sq.mm. Conforming to RDSO Specification No. ETI/OHE/50 (6/97) with A&C slip No.1 with latest modification	2500KGS./13	500	26800
2	04165003	05-JAN-17	(PL_NO:4005N5) 33KV (E) Stranded, Compact circular aluminium conductor, conductor screened with extruded semiconducting compound, XLPE insulated, insulation screened with extruded, semiconducting compound in combination with copper tape cores laid UP, inner sheathed Galvanized steel strip armoured and overall PVC sheathed black cable conforming to IS: 7098/II/1985 with latest amendments size 3x300 sq.mm. (PL_NO:4005N3) Supply of ISI mark 11KV (E) Stranded, compact circular aluminum conductor, conductor screened with extruded semi conducting compound, XLPE insulated, insulation screened with extruded semi conducting compound in combination with copper tape cores laid up, inner sheathed, galvanized steel strip armored, and overall PVC sheathed black cable conforming to IS : 7098/II/2011 with latest amandment size 3x240 Sq. mm.(Make Polycab, Havels, Fort Gloster, Finolex, Torrent etc with ISI marked )	10000MTR/22 1650MTR/22	2500	500000

Sr.No	Tender No	Tender Opening Date	Description	QTY	Tender Cost	Emd Amount
			(PL_NO:4005N2) Supply of ISI 33KV (E) stranded compact circular Aluminium conductor, conductor screened with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi- conducting compound in combination with copper tape, Cores laid up , inner sheath of PVC tape, galvanised flat steel strip armoured and overall PVC sheathed cable conforming to IS 7098/ (part-II) 2011 with latest amendments; Size 3x400 sq mm; (Make Polycab,Havels,Torrent, Fort Gloster,Finolex etc with ISI mark)	5520MTR/22		
			(PL_NO:4005N4) ISI Marked cross linked polyethelene (XLPE) HT cable outer sheathed insulated armoured with galvanized round steel wire with alumunium conductor suitable for rated voltage at 11000 Volts grade and conforming to IS-7098/II/2011 with latest amendment size 3x120 sq mm.	500MTR/22		
			(PL_NO:4005N1) HT Cable,11 KV (E) Stranded, compact circular aluminium conductor, conductor screened with extruded semi conducting compound, XLPE insulated, insulated screened with extruded semi connducting compound in combination with copper tape cord laid up, innnner sheathed, galvanised steel strip armoured, and overall PVC sheathed black cable conforming to IS: 7098/II/2011 with latest ammendments if any, size : 3 x 120 sq.mm.	2500MTR/22		
			(PL_NO:4005N) 11KV (E) stranded, compact circular aluminium conductor, conductor screened with extruded semi conducting compound, XLPE insulated screened with extuded semiconducting compound in combination with copper tape cores laid up, inner sheathed, galvanized steel armoured and overall PVC sheathed black cable conforming to IS:7098/II/2011 with latest amendments size 3x240 sq.mm.	4500MTR/22		
3	06161685	05-JAN-17	(PL_NO:79315689) ISI marked Safety foot wear of anti skid and oil resistant type for professional use as per IS: 15298/2011 Pt-I & II or its latest as per technical Specification: - Design: LOW/DERBY colour Black, Full Grain leather (1.9 MM to 2 MM), polyurethane (PU) Single Density/Direct Injection Sole, Cleated outsole, Insole: Thickness shall be not less than 2.0 MM, Steel toe cap to IS: 5852/96, Textiles Lining, Socks padding: 3MM Minimum, Collar padding: 12 MM Minimum, Stitching: 4 to 6 Ply Nylon lace, 80 MM long Nylon laces, ISI Marking and Year of the manufacturing	1596PAIRS/02	1500	101300

Sr.No	Tender No	Tender Opening Date	Description	QTY	Tender Cost	Emd Amount
			must be stamped on each shoe, Each of the shoes must be wrapped in a paper and packed separately in a card board packing box, Electrical resistance: 100 kilo ohms to 1000 mega ohms.			
			(PL_NO:79315689) ISI marked Safety foot wear of anti skid and oil resistant type for professional use as per IS: 15298/2011 Pt-I & II or its latest as per technical Specification: - Design: LOW/DERBY colour Black, Full Grain leather (1.9 MM to 2 MM), polyurethane (PU) Single Density/Direct Injection Sole, Cleated outsole, Insole: Thickness shall be not less than 2.0 MM, Steel toe cap to IS: 5852/96, Textiles Lining, Socks padding: 3MM Minimum, Collar padding: 12 MM Minimum, Stitching: 4 to 6 Ply Nylon lace, 80 MM long Nylon laces, ISI Marking and Year of the manufacturing must be stamped on each shoe, Each of the shoes must be wrapped in a paper and packed separately in a card board packing box, Electrical resistance: 100 kilo ohms to 1000 mega ohms.	1400PAIRS/02		
			(PL_NO:79315689) ISI marked Safety foot wear of anti skid and oil resistant type for professional use as per IS: 15298/2011 Pt-I & II or its latest as per technical Specification: - Design: LOW/DERBY colour Black, Full Grain leather (1.9 MM to 2 MM), polyurethane (PU) Single Density/Direct Injection Sole, Cleated outsole, Insole: Thickness shall be not less than 2.0 MM, Steel toe cap to IS: 5852/96, Textiles Lining, Socks padding: 3MM Minimum, Collar padding: 12 MM Minimum, Stitching: 4 to 6 Ply Nylon lace, 80 MM long Nylon laces, ISI Marking and Year of the manufacturing must be stamped on each shoe, Each of the shoes must be wrapped in a paper and packed separately in a card board packing box, Electrical resistance: 100 kilo ohms to 1000 mega ohms.	1855PAIRS/02		
			(PL_NO:79315689) ISI marked Safety foot wear of anti skid and oil resistant type for professional use as per IS: 15298/2011 Pt-I & II or its latest as per technical Specification: - Design: LOW/DERBY colour Black, Full Grain leather (1.9 MM to 2 MM), polyurethane (PU) Single Density/Direct Injection Sole, Cleated outsole, Insole: Thickness shall be not less than 2.0 MM, Steel toe cap to IS: 5852/96, Textiles Lining, Socks padding: 3MM Minimum, Collar	424PAIRS/02		

Sr.No	Tender No	Tender Opening Date	Description	QTY	Tender Cost	Emd Amount
			padding: 12 MM Minimum, Stitching: 4 to 6 Ply Nylon lace, 80 MM long Nylon laces, ISI Marking and Year of the manufacturing must be stamped on each shoe, Each of the shoes must be wrapped in a paper and packed separately in a card board packing box, Electrical resistance: 100 kilo ohms to 1000 mega ohms. (PL_NO:79315689) ISI marked Safety foot wear of anti skid and oil resistant type for professional use as per IS: 15298/2011 Pt-I & II or its latest as per technical Specification: - Design: LOW/DERBY colour Black, Full Grain leather (1.9 MM to 2 MM), polyurethane (PU) Single Density/Direct Injection Sole, Cleated outsole, Insole: Thickness shall be not less than 2.0 MM, Steel toe cap to IS: 5852/96, Textiles Lining, Socks padding: 3MM Minimum, Collar padding: 12 MM Minimum, Stitching: 4 to 6 Ply Nylon lace, 80 MM long Nylon laces, ISI Marking and Year of the manufacturing must be stamped on each shoe, Each of the shoes must be wrapped in a paper and packed separately in a card board packing box, Electrical resistance: 100 kilo ohms to 1000 mega ohms. (PL_NO:79315689) ISI marked Safety foot wear of anti skid and oil resistant type for professional use as per IS: 15298/2011 Pt-I & II or its latest as per technical Specification: - Design: LOW/DERBY colour Black, Full Grain leather (1.9 MM to 2 MM), polyurethane (PU) Single Density/Direct Injection Sole, Cleated outsole, Insole: Thickness shall be not less than 2.0 MM, Steel toe cap to IS: 5852/96, Textiles Lining, Socks padding: 3MM Minimum, Collar padding: 12 MM Minimum, Stitching: 4 to 6 Ply Nylon lace, 80 MM long Nylon laces, ISI Marking and Year of the manufacturing must be stamped on each shoe, Each of the shoes must be wrapped in a paper and packed separately in a card board packing box, Electrical resistance: 100 kilo ohms to 1000 mega ohms. (PL_NO:79315689) ISI marked Safety foot wear of anti skid and oil resistant type for professional use as per IS: 15298/2011 Pt-I & II or its latest as per technical Specification: - Design: LOW/DERBY colour Black, Full Grain leather (1.9 MM to 2 MM), polyurethane (PU) Single Density/Direct Injection Sole, Cleated outsole, Insole: Thickness shall be not less than 2.0 MM, Steel toe cap to IS: 5852/96, Textiles Lining, Socks padding: 3MM Minimum, Collar	3687PAIRS/02		
			padding: 12 MM Minimum, Stitching: 4 to 6 Ply Nylon lace, 80 MM long Nylon laces, ISI Marking and Year of the manufacturing must be stamped on each shoe, Each of the shoes must be wrapped in a paper and packed separately in a card board packing box, Electrical resistance: 100 kilo ohms to 1000 mega ohms. (PL_NO:79315689) ISI marked Safety foot wear of anti skid and oil resistant type for professional use as per IS: 15298/2011 Pt-I & II or its latest as per technical Specification: - Design: LOW/DERBY colour Black, Full Grain leather (1.9 MM to 2 MM), polyurethane (PU) Single Density/Direct Injection Sole, Cleated outsole, Insole: Thickness shall be not less than 2.0 MM, Steel toe cap to IS: 5852/96, Textiles Lining, Socks padding: 3MM Minimum, Collar padding: 12 MM Minimum, Stitching: 4 to 6 Ply Nylon lace, 80 MM long Nylon laces, ISI Marking and Year of the manufacturing must be stamped on each shoe, Each of the shoes must be wrapped in a paper and packed separately in a card board packing box, Electrical resistance: 100 kilo ohms to 1000 mega ohms. (PL_NO:79315689) ISI marked Safety foot wear of anti skid and oil resistant type for professional use as per IS: 15298/2011 Pt-I & II or its latest as per technical Specification: - Design: LOW/DERBY colour Black, Full Grain leather (1.9 MM to 2 MM), polyurethane (PU) Single Density/Direct Injection Sole, Cleated outsole, Insole: Thickness shall be not less than 2.0 MM, Steel toe cap to IS: 5852/96, Textiles Lining, Socks padding: 3MM Minimum, Collar padding: 12 MM Minimum, Stitching: 4 to 6 Ply Nylon lace, 80 MM long Nylon laces, ISI Marking and Year of the manufacturing must be stamped on each shoe, Each of the shoes must be wrapped in a paper and packed separately in a card board packing box, Electrical resistance: 100 kilo ohms to 1000 mega ohms. (PL_NO:79315689) ISI marked Safety foot wear of anti skid and oil resistant type for professional use as per IS: 15298/2011 Pt-I & II or its latest as per technical Specification: - Design: LOW/DERBY colour Black, Full Grain leather (1.9 MM to 2 MM), polyurethane (PU) Single Density/Direct Injection Sole, Cleated outsole, Insole: Thickness shall be not less than 2.0 MM, Steel toe cap to IS: 5852/96, Textiles Lining, Socks padding: 3MM Minimum, Collar	627PAIRS/02		
			padding: 12 MM Minimum, Stitching: 4 to 6 Ply Nylon lace, 80 MM long Nylon laces, ISI Marking and Year of the manufacturing must be stamped on each shoe, Each of the shoes must be wrapped in a paper and packed separately in a card board packing box, Electrical resistance: 100 kilo ohms to 1000 mega ohms. (PL_NO:79315689) ISI marked Safety foot wear of anti skid and oil resistant type for professional use as per IS: 15298/2011 Pt-I & II or its latest as per technical Specification: - Design: LOW/DERBY colour Black, Full Grain leather (1.9 MM to 2 MM), polyurethane (PU) Single Density/Direct Injection Sole, Cleated outsole, Insole: Thickness shall be not less than 2.0 MM, Steel toe cap to IS: 5852/96, Textiles Lining, Socks padding: 3MM Minimum, Collar padding: 12 MM Minimum, Stitching: 4 to 6 Ply Nylon lace, 80 MM long Nylon laces, ISI Marking and Year of the manufacturing must be stamped on each shoe, Each of the shoes must be wrapped in a paper and packed separately in a card board packing box, Electrical resistance: 100 kilo ohms to 1000 mega ohms. (PL_NO:79315689) ISI marked Safety foot wear of anti skid and oil resistant type for professional use as per IS: 15298/2011 Pt-I & II or its latest as per technical Specification: - Design: LOW/DERBY colour Black, Full Grain leather (1.9 MM to 2 MM), polyurethane (PU) Single Density/Direct Injection Sole, Cleated outsole, Insole: Thickness shall be not less than 2.0 MM, Steel toe cap to IS: 5852/96, Textiles Lining, Socks padding: 3MM Minimum, Collar	803PAIRS/02		

Sr.No	Tender No	Tender Opening Date	Description	QTY	Tender Cost	Emd Amount
4	06165103	05-JAN-17	padding: 12 MM Minimum, Stitching: 4 to 6 Ply Nylon lace, 80 MM long Nylon laces, ISI Marking and Year of the manufacturing must be stamped on each shoe, Each of the shoes must be wrapped in a paper and packed separately in a card board packing box, Electrical resistance: 100 kilo ohms to 1000 mega ohms. (PL_NO:6579N) Battery Charger for Charging of locomotive batteries, Technical Specification as per Annexure enclosed.	1NOS./01		8400
5	03161390	06-JAN-17	(PL_NO:38146629) Equalising lever With Bushes To RDSO's SK.- 69597, Item. No.- 1,5,6&7 Alt. 41(Forty One ). Material and specification as per drawing.	1373NOS./01	500	22000
6	04162400	06-JAN-17	(PL_NO:43980144) LED Flood Light complete fitting with Lamp 90 watt, as per Annexure.	51NOS./01	500	48300
			(PL_NO:43980144) LED Flood Light complete fitting with Lamp 90 watt, as per Annexure.	13NOS./01		
			(PL_NO:43980144) LED Flood Light complete fitting with Lamp 90 watt, as per Annexure.	100NOS./01		
7	05161315	06-JAN-17	(PL_NO:50980026) 2 Mbps Digital Modem (Line Driver) as per RDSO specification No. RDSO/SPN/TC/80/2013 Rev. 1.0	55PAIRS/02	500	26300

railway reserves the right to issue any corrigendum to the tenders. Complete details available at [www.ireps.gov.in](http://www.ireps.gov.in) and [www.secr.gov.in](http://www.secr.gov.in), In case of any discrepancy between the tender document downloaded from internet and the master copy available in the office, the latter shall prevail and will be binding on the tenderer(s) NO claim on this account will be entertained. For any clarification related to 'e'-procurement, tenderers are requested to contact Dy.CMM-IT or AMM-IC at phone Nos:-07752-415302, 07752-411349.

**Controller of Stores**  
**S.E.C.Railway/Bilaspur**